



UNITED STATES PATENT AND TRADEMARK OFFICE

cen

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/919,845	08/02/2001	Sharon Barkai	1031-US	5670

24505 7590 03/21/2007
DANIEL J SWIRSKY
55 REUVEN ST.
BEIT SHEMESH, 99544
ISRAEL

EXAMINER

MAIS, MARK A

ART UNIT	PAPER NUMBER
----------	--------------

2616

SHORTENED STATUTORY PERIOD OF RESPONSE	MAIL DATE	DELIVERY MODE
3 MONTHS	03/21/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

If NO period for reply is specified above, the maximum statutory period will apply and will expire 6 MONTHS from the mailing date of this communication.

Office Action Summary

Application No.

09/919,845

Applicant(s)

BARKAI ET AL.

Examiner

Mark A. Mais

Art Unit

2616

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 17 January 2007.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims

- 4) ☒ Claim(s) 1-8 is/are pending in the application.
- 4a) Of the above claim(s) _____ is/are withdrawn from consideration.
- 5) ☐ Claim(s) _____ is/are allowed.
- 6) ☒ Claim(s) 1-8 is/are rejected.
- 7) ☐ Claim(s) _____ is/are objected to.
- 8) ☐ Claim(s) _____ are subject to restriction and/or election requirement.

Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on _____ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some * c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
 2. ☐ Certified copies of the priority documents have been received in Application No. _____.
 3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

* See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- | | |
|--|---|
| 1) <input checked="" type="checkbox"/> Notice of References Cited (PTO-892) | 4) <input type="checkbox"/> Interview Summary (PTO-413)
Paper No(s)/Mail Date. _____ |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)
Paper No(s)/Mail Date _____ | 6) <input type="checkbox"/> Other: _____ |

DETAILED ACTION

Claim Rejections - 35 USC § 102

1. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

(e) the invention was described in a patent granted on an application for patent by another filed in the United States before the invention thereof by the applicant for patent, or on an international application by another who has fulfilled the requirements of paragraphs (1), (2), and (4) of section 371(c) of this title before the invention thereof by the applicant for patent.

2. The changes made to 35 U.S.C. 102(e) by the American Inventors Protection Act of 1999 (AIPA) and the Intellectual Property and High Technology Technical Amendments Act of 2002 do not apply when the reference is a U.S. patent resulting directly or indirectly from an international application filed before November 29, 2000. Therefore, the prior art date of the reference is determined under 35 U.S.C. 102(e) prior to the amendment by the AIPA (pre-AIPA 35 U.S.C. 102(e)).

3. Claims 1, 2 and 8 are rejected under 35 U.S.C. 102(e) as being anticipated by Nordenstam et al. (USP 6,687,748).

Art Unit: 2616

4. With regard to claims 1 and 8, Nordenstam et al. discloses determining *the path that a network message would take among network devices* in a computer network [**simulates calls, routing, and establishments procedures (interpreted as simulated network messages), col. 12, lines 56-62**] the method comprising:

Providing a plurality of device components to model a physical computer network, each of said device components modeling an aspect of a network device of said physical computer network [**modeling the virtual network based on the multiple real links, col. 10, lines 3-7; Figs. 7a-d, different network topologies**];

simulating sending a network message [**simulates calls, routing, and establishments procedures (interpreted as simulated network messages), col. 12, lines 56-62**] within *said model of said computer network* [**virtual network, col. 5, lines 27-35**] from a source device component *modeling one of said network devices of said physical network* [**Figs. 7a-d, Source A**] to a destination device component [**Figs. 7a-d, Destination B**] along a device component path [**Figs. 7a-d, the path between Source A and Destination B**],

wherein *said simulated message* [**simulates calls, routing, and establishments procedures (interpreted as simulated network messages), col. 12, lines 56-62**] *only traverses any of said devices which model said network devices of said physical computer network* [**only routed virtually along the best route, col. 9, lines 15-19; can even use different system configuration, col. 11, lines 1-5**] and

recording the device components traversed by *said simulated message within said model of said physical computer network*, thereby determining *path that said network message would take among said network devices in said physical computer network* as well as the validity of the

Art Unit: 2616

path [interpreted as the path the network's simulated messages go for simulated calls, routing, and establishment procedures (setup/teardown), col. 12, lines 56-62; thus, traffic is modeled on the virtual network where the simulated links correspond to real links, col. 9, line 66 to col. 10, line 11].

5. With regard to claim 2, Nordenstam et al. discloses further comprising

providing the model with a plurality of agents [**modeling the virtual network based on the multiple real links, col. 10, lines 3-7; Figs. 7a-d, different network topologies**]

each agent [**modeling the virtual network based on the multiple real links, col. 10, lines 3-7**] corresponding to a destination network element [**Figs. 7a-d, Destination B**] of said computer network comprising a plurality of network elements, and

said plurality of device components (DC) [**modeling the virtual network based on the multiple real links, col. 10, lines 3-7; Figs. 7a-d, different network topologies**], each of said device components modeling at least one aspect of one of said network elements, said aspect being either of a physical and a functional characteristic of said network element [**can simulate calls, routing, and establishment procedures (setup/teardown), col. 12, lines 56-62; thus, traffic is modeled on the virtual network where the simulated links correspond to real links, col. 9, line 66 to col. 10, line 11**],

wherein each of said agents comprises a plurality of said device components [**modeling the virtual network based on the multiple real links, col. 10, lines 3-7; Figs. 7a-d, different network topologies**], and

wherein at least two of said device components **[Figs. 7a-d, Source A and Destination B]** within at least one of said agents are logically interconnected **[Figs. 7a-d, different network topologies]**, each logical interconnection corresponding to either of a physical and a functional interconnection found within or between any of said network elements **[modeling the virtual network based on the multiple real links, col. 10, lines 3-7; Figs. 7a-d, different network topologies]**.

Claim Rejections - 35 USC § 103

6. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

7. Claims 3-7 are rejected under 35 U.S.C. 103(a) as being unpatentable over Nordenstam et al. as applied to claims 1, 2, and 8 above, and further in view of Hao et al. (USP 6,728,214).

8. With regard to claims 3-4, Nordenstam et al. discloses a that the *simulating* sending step **[simulates calls, routing, and establishments procedures (interpreted as simulated network messages), col. 12, lines 56-62]** comprises each device component along the device component path traversed by the message **[traffic is modeled on the virtual network where the simulated**

Art Unit: 2616

links correspond to real links, col. 9, line 66 to col. 10, line 11]. Nordenstam et al. discloses that the simulated device components performs routing (and is therefore interpreted as a router) **[interpreted as the path the network's simulated messages go for simulated calls, routing, and establishment procedures (setup/teardown), col. 12, lines 56-62; thus, traffic is modeled on the virtual network where the simulated links correspond to real links, col. 9, line 66 to col. 10, line 11].**

Nordenstam et al. does not specifically disclose identifying an intermediate device component along the device component path to which the message is to be passed and passing the message and an identifier of the intermediate device component to an immediately next device component in accordance with network routing rules. However, Hao et al. discloses testing network routers by simulating the network topologies **[see Title and Abstract]**. Hao et al. randomly inserts/deletes either an edge (connection), router-node or network node, checks the network topology and routing tables, and further checks the packet forwarding behavior **[col. 4, line 54 to col. 5, line 35; especially with IP protocols such RIP, OSPF, and BGP, col. 5, lines 38-40]**. A packet (such as an IP packet), sent from a first router, via a route containing multiple routers, must be received correctly by the destination router **[col. 7, lines 10-19]**. Since the router-under-test (RUT) has a changing network topology, it must constantly simulate updating the presence of device components [e.g., routing tables], then possibly the absence of device components via a network topology table **[col. 4, lines 30-36]** as if it were in a real network **[col. 3, lines 31-35]**, and, therefore, whether the tested router is complying with the network routing rules. Thus, it would have been obvious to one of ordinary skill in the art at the time of the invention to have modified the router of Nordenstam et al. to include the specific functionality of

Art Unit: 2616

the router-testing of Hao et al. because such a testing method would allow the network management system to be properly tested for scalability, performance, and reliability while still not incurring the monetary and time burdens that accompany all the network devices in a network environment [see Nordenstam et al., col. 1, lines 2, lines 13-25].

9. With regard to claim 5, Nordenstam et al. discloses a that the *simulating* sending step [simulates calls, routing, and establishments procedures (interpreted as simulated network messages), col. 12, lines 56-62] comprises each device component along the device component path traversed by the message [traffic is modeled on the virtual network where the simulated links correspond to real links, col. 9, line 66 to col. 10, line 11]. Nordenstam et al. discloses that the simulated device components performs routing (and is therefore interpreted as a router) [interpreted as the path the network's simulated messages go for simulated calls, routing, and establishment procedures (setup/teardown), col. 12, lines 56-62; thus, traffic is modeled on the virtual network where the simulated links correspond to real links, col. 9, line 66 to col. 10, line 11].

Nordenstam et al. does not specifically disclose identifying the intermediate device component within the same network layer. However, Hao et al. discloses testing network routers by simulating the network topologies [see Title and Abstract]. Hao et al. randomly inserts/deletes either an edge (connection), router-node or network node, checks the network topology and routing tables, and further checks the packet forwarding behavior [col. 4, line 54 to col. 5, line 35; especially with IP protocols such RIP, OSPF, and BGP, col. 5, lines 38-40]. A packet (such as an IP packet), sent from a first router, via a route containing multiple routers,

Art Unit: 2616

must be received correctly by the destination router [col. 7, lines 10-19]. Since the router-under-test (RUT) has a changing network topology, it must constantly simulate updating the presence of device components [e.g., routing tables], then possibly the absence of device components via a network topology table [col. 4, lines 30-36] as if it were in a real network [col. 3, lines 31-35], and, therefore, whether the tested router is complying with the network routing rules. Thus, Hao et al. discloses identifying the intermediate device component within the same network layer because it inserts/deletes connections and then checks the network topology, routing tables, and checks packet forwarding [col. 4, line 54 to col. 5, line 35; especially with IP protocols such **RIP, OSPF, and BGP, col. 5, lines 38-40**]. Thus, it would have been obvious to one of ordinary skill in the art at the time of the invention to have modified the router of Nordenstam et al. to include the specific functionality of the router-testing of Hao et al. because such a testing method would allow the network management system to be properly tested for scalability, performance, and reliability while still not incurring the monetary and time burdens that accompany all the network devices in a network environment [see Nordenstam et al., col. 1, lines 2, lines 13-25].

10. With regard to claim 6, Nordenstam et al. discloses a that the *simulating* sending step **[simulates calls, routing, and establishments procedures (interpreted as simulated network messages), col. 12, lines 56-62]** comprises each device component along the device component path traversed by the message **[traffic is modeled on the virtual network where the simulated links correspond to real links, col. 9, line 66 to col. 10, line 11]**. Nordenstam et al. discloses that the simulated device components performs routing (and is therefore interpreted as a router) **[interpreted as the path the network's simulated messages go for simulated calls, routing,**

Art Unit: 2616

and establishment procedures (setup/teardown), col. 12, lines 56-62; thus, traffic is modeled on the virtual network where the simulated links correspond to real links, col. 9, line 66 to col. 10, line 11]:

Nordenstam et al. does not specifically disclose receiving the message at the immediately next device component and performing different functions based on what network layer the next device component is in. However, Hao et al. discloses testing network routers by simulating the network topologies [see Title and Abstract]. Hao et al. randomly inserts/deletes either an edge (connection), router-node or network node, checks the network topology and routing tables, and further checks the packet forwarding behavior [col. 4, line 54 to col. 5, line 35; especially with IP protocols such RIP, OSPF, and BGP, col. 5, lines 38-40]. A packet (such as an IP packet), sent from a first router, via a route containing multiple routers, must be received correctly by the destination router [col. 7, lines 10-19]. Since the router-under-test (RUT) has a changing network topology, it must constantly simulate updating the presence of device components [e.g., routing tables], then possibly the absence of device components via a network topology table [col. 4, lines 30-36] as if it were in a real network [col. 3, lines 31-35], and, therefore, whether the tested router is complying with the network routing rules.

Thus, Hao et al. discloses receiving the message at the immediately next device component [Fig. 12, simulated network topology shows the multiples routers between the RUT and the further routers/networks]; if the message is received from a device component at a higher network layer [for BGP testing, the testing involves setting up a higher layer TCP connection, then sending update packets to the RUT, col. 11, lines 12-18]; placing information onto an information stack as may be needed by any device component along the

Art Unit: 2616

device component path to identify other device components along the device component path to which the message is to be passed **[Each BGP router maintains its preferred paths to all possible destinations (not necessarily the shortest path), the BGP router must advertise these paths to its adjacent multiple routers, col. 9, lines 48-53. Since the information identifying intermediate nodes is extracted via the virtual/testing environment, examiner interprets placing the information onto a stack as passing the intermediate node information to the RUT from the original device component path (e.g., Fig. 12, from the farthest BGP router to the RUT); thus, each possible destination node is exchanged, col. 9, lines 60-65];** and if the message is received from a device component at a lower network layer **[in OSPF, lower level LSA advertisements are sent out concerning each router's own network connections, col. 8, lines 57-65];** removing information from the information stack needed to identify a subsequent intermediate device component along the device component path to which the message is to be passed **[each OSPF router exchanges "hello" packets to maintain adjacency and LSAs to describe its own network connections and learned routes, col. 8, lines 57-65. Since the information identifying intermediate nodes is extracted via the virtual/testing environment, the examiner interprets removing information from the stack as passing the intermediate node information to the RUT from the original device component path (e.g., Fig. 12, from the farthest OSPF router to the RUT); thus, the current network topology is exchanged, col. 8, line 66 to col. 9, line 4.].** Thus, it would have been obvious to one of ordinary skill in the art at the time of the invention to have modified the router of Nordenstam et al. to include the specific functionality of the router-testing of Hao et al. because such a testing method would allow the network management system to be properly

Art Unit: 2616

tested for scalability, performance, and reliability while still not incurring the monetary and time burdens that accompany all the network devices in a network environment [see **Nordenstam et al.**, col. 1, lines 2, lines 13-25].

11. With regard to claim 7, Hao et al. further discloses using the removed stack information [the removed stack information is used to generate the LSA to the RUT and test whether the network topology and learned routes, col. 9, lines 8-39].

Response to Arguments

12. Applicant's arguments with respect to claims 1-8 have been considered but are moot in view of the new ground(s) of rejection.

Conclusion

13. Accordingly, Applicant's amendment necessitated the new grounds of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

14. A shortened statutory period for reply to this final action is set to expire **THREE MONTHS** from the mailing date of this action. In the event a first reply is filed within **TWO MONTHS** of

Art Unit: 2616

the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

15. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure:

(a) Wang (USP 6,845,352), Framework for flexible and scaleable real-time traffic emulation for packet switched networks.

16. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Mark A. Mais whose telephone number is 572-272-3138. The examiner can normally be reached on M-Th 5am-4pm.

17. If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Seema Rao can be reached on 571-272-3174. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2616

18. Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

MAM

March 4, 2007

Seema S. Rao
SEEMA S. RAO 3/19/07
SUPERVISORY PATENT EXAMINER
TECHNOLOGY CENTER 2600